

PRESYS®

PSV PORTABLE STATION

A family of compact, digital, easy operated and portable stations, for test and calibration of safety and relief valves, with connections from ½" to 6".



www.presys.com.br

PSV STATION

PSV STATION

Equipped with a data acquisition system that allows automatic detection of opening pressures (SET).

The **PRESYS** PSV portable station is a complete solution, composed of portable a test table and a control case that communicates with the calibration software Isoplan-5[®], emitting complete and detailed certificates and test reports for pressure safety valves (PSV) and pressure relief valves (PRV).

Pneumatic.

Configurable Digital indicator according to the engineering unit of the tested valve.

Available units: psi, bar, MPa, kPa, kgf/cm², gf/cm² (others units under consult).

Easy to install and ready to use.

Nitrogen or air operated.

PRESSURE RANGES AVAILABLE*

500 psig (35 bar) / 1000 psig (70 bar) / 3000 psig (210 bar)

**other pressures on request*

STANDARD FEATURES

- ❑ AUTOMATIC ACQUISITION of SET Pressure value.
- ❑ 0.1 % FS High accuracy digital pressure acquisition and measurement system.
- ❑ Calibration certificates for all pressure indicators.
- ❑ Pressurized valve sinalization.
- ❑ Threaded valves up to 2", with set thread female NPT adapter's kit for up to 3000 psi (210 bar).
- ❑ Mounting flanged valves: from 1" (DN 25) to 6" (DN 150).
- ❑ Easy to operated control panel with precision regulator for fine adjustment of pressure.
- ❑ Manual clamping system with up to 4 clamps.
- ❑ Output for external pressure standard gauge with fast connection – tool free. It can be used as gauge calibration port.
- ❑ Dimensions: Carrying case: 470 x 357 x 176mm - Table: 542 x 530 x 210mm
- ❑ Carrying case: 10 kg - Table: 22 kg - Table with accessories: 45 kg.

INCLUDED ACCESSORIES

Set thread female NPT adapters

Sizes:
1/2", 3/4", 1", 1 1/4", 1 1/2" e 2".
Maximum pressure up to 3000 psi (210 bar)
Other size/pressure, under consult.



Manual clamping system



Flange adapters for test

For test flanged valves from 1/2" (DN 15) to (DN 150) With polyurethane O-ring gasket.



COMPANY: PRESYS INSTRUMENTS CO.	REG. NUMBER: CRN 0671550
INSTRUMENT: SAFETY VALVE	TAG: PSV-1231004 - 10 bar
FUNCT.: BOILER PROTECTION	CALIBRATION PERIOD: 12 Months
SECTOR: PLANT BOILER 1	
CRITICALITY: SECURITY	
O.S.: SAP001	PROC.: P-03104

PROCESS OPERATION INFORMATION

Associated Equipment ID: 407	Operating Temperature: Not Informed
Operating Pressure: Not Informed	FMTP: Not Informed

INSTRUMENT SPECIFICATION

Manufacturer: HANSEN USA	Fluid: AIR
Model: HANSEN USA	Body Material: ST316L
Fluid Azote: N/A	Seat Material: STAINLESS STEEL
Input Connection: 2 1/2"	Pressure Class: 150#
Output Connection: 3"	Manufacturing Standard: ASME VIII
Thread or Flange Connection: FLANGED	Heic: F

CALIBRATION AND ADJUSTMENT

INITIAL CALIBRATION

	Reference (bar)	Reading 1 (bar)	Average (bar)	Error (bar)	Blowdown (%)	U (bar)
SET PRESSURE	11,00	10,76	10,70	0,30	43,93	0,14
RESEATING PRESSURE	6,50	6,00	6,00	-0,50		

Leakage: LEAKING Internal State: GOOD

FINAL CALIBRATION

	Reference (bar)	Reading 1 (bar)	Reading 2 (bar)	Reading 3 (bar)	Average (bar)	Error (bar)	Blowdown (%)
SET PRESSURE	11,00	10,76	10,76	10,74	10,75	-0,25	42,1
RESEATING PRESSURE	6,50	6,25	6,06	6,16	6,16	-0,34	

COMMENTS:

-Used Norm: ASME VIII (Gas)

SUMMARY OF PERFORMED SERVICES

PARTS REPLACED: SEATS	NOZZLE: MACHINED
SEAT: GRINDING, LAPPING	SPRING: VERIFIED
STEM: POLISHED	UPPER SEALING: SEALED
CLEANING SOLVENT, SANDBLASTED	LOWER SEALING: SEALED
PAINTING: ALUMINUM 600°C	

LEAK TEST

FLUID: AIR	NUMBER OF BUBBLES: 2	MINUTES:
------------	----------------------	----------

SHIFTING LIFT

GOOD

CALIBRATION CONDITIONS

LOCATION: PRESYS MAINTENANCE LABORATORY	TEMPERATURE: 23°C
HUMIDITY: 60%	PRESYS 1 atm

USED STANDARDS

MODEL: DMY-2017-Lpha-1112-0-0-3-0-1 S.N.: 005.09.15 Cat. N.: R3060.07.15 Next Calib.: 15/09/2016 Scale: Pressure PSV 0

INITIAL DIAG.: Not Approved FINAL DIAG.: Approved

CALIBRATION: 18/02/2016 NEXT: 18/02/2017


COMMENTS

Used Norm: ASME VIII (Gas)

CERTIFICATE

COMPANY: PRESYS INSTRUMENTS CO.	REG. NUMBER: CRN 0671550
INSTRUMENT: SAFETY VALVE	TAG: PSV-1231004 - 10 bar
FUNCT.: BOILER PROTECTION	CALIBRATION PERIOD: 12 Months
SECTOR: PLANT BOILER 1	
CRITICALITY: SECURITY	
O.S.: SAP001	PROC.: P-03104

CALIBRATION GRAPHIC



PHOTOGRAPHIC REPORT



[Signature]
 Juan Mac
 18/02/2016 17:00:00

[Signature]
 Wilson Johnson
 18/02/2016 17:00:12

The set pressure is automatically registered and display on the digital pressure registration system and can be send in real-time to the ISOPLAN® Software.

ISOPLAN® calibration software allows you to record all your safety valves technical information and calibration operations in a strong database in order to meet your safety regulations.

It will generate the full calibration report that will include the calibration graphics, photos of the valve before and after maintenance as well as any technical relevant information.

PRESYS PSV Workstation is delivered ready to use and we provide training by internet conference or on-site on request. **PRESYS** products are developed in a technology context combining high quality and reliability, using a continuous improvement process. With a global presence in most regions of the world, directly or with specialized and trained distributors, **PRESYS** provides you with the right solution for you application or calibration needs, always benefiting of our entire technical support.