

Accessories for PCON Pressure Controller

Contamination Trap

- They protect the pneumatic calibrator against the ingress of debris (oil, water, etc.) present in the connected process instruments to the PCON. These residues can affect pressure control, damaging the PCON and even voiding the warranty.

For FS version up to 40 bar



Model: SI-600-FS-S

- Ordering Code: **06.08.0134-00.**
- For FS version up to 25 bar.
- Maximum Pressure: 600 psi (40 bar).

Model: SI-600-FS-L

- Ordering Code: **06.08.0135-00.**
- For FS versions from 30 to 40 bar.
- Maximum Pressure: 600 psi (40 bar).



For the FS/RM version with 70 bar, it has a reduced internal volume.

- It reduces the operating time of the internal compressor, increasing its lifespan.

Model: SI-1000-FS

- Ordering Code: **06.08.0103-00.**
- For the 70 bar FS version.
- Maximum Pressure: 1000 psi (70 bar).

Model: SI-1000-RM

- Ordering Code: **06.08.0136-00.**
- Ideal for the 70 bar RM version.
- Maximum Pressure: 1000 psi (70 bar).



For large quantities of calibrations

- Ideal for benchtop applications using the PCON with power supply externa de ar, devido possuir um maior volume interno.

Model: SI-600

- Ordering Code: **06.08.0090-00.**
- Ideal for RM versions up to 40 bar.
- Maximum Pressure: 600 psi (40 bar).

Model: SI-3000

- Ordering Code: **06.08.0095-00.**
- Ideal for RM or FS versions working with External air supply (has a large internal volume).
- External air supply (has a large internal volume)..



Expandable Manifold Kit

- Ordering Code: **02.09.0155-00.**
- Material: Anodized aluminum block, support in painted aluminum.
- Maximum Pressure: 3000 psi (210 bar).

